



### REMACHE DE HIERRO CABEZA REDONDA

Código	Diámetro "D" pulg - mm	Largo Pulg mm	Envase	Díametro "A" mm	Altura "H" mm	Rango de Agarre, mm	Díametro Broca, mm	Nº piezas por kilo (*)
01RFR	1/8" - 3,1	1/4	6,3	5.5 - 5.9	2.2 - 2.5	1,9 - 3,2	3.5	1.428
02RFR		3/8	9,5			5,0 - 6,4		1.064
03RFR		1/2	12,7			8,2 - 9,6		942
04RFR		5/8	15,8			11,4 - 12,7		667
05RFR		3/4	19,0			14,6 - 15,9		633
06RFR		1"	25,4			20,9 - 22,3		588
07RFR		1 1/4	31,7			27,3 - 28,6		465
08RFR	3/16" - 4,7	3/8	9,5	8.2 - 8.8	3.4 - 3.7	2,8 - 4,8	5.0	444
09RFR		1/2	12,7			5,9 - 8,0		370
10RFR		5/8	15,8			9,1 - 11,2		323
11RFR		3/4	19,0			12,3 - 14,3		282
12RFR		1"	25,4			18,6 - 20,7		221
13RFR		1 1/4	31,7			25,0 - 27,0		185
14RFR		1 1/2	38,1			31,3 - 33,4		167
15RFR		1 3/4	44,4			37,7 - 39,7		139
16RFR	2"	50,8	44,0 - 46,1	122				
17RFR	1/4" - 6,3	3/8	9,5	10.9 - 11.6	4.6 - 4.9	0,8 - 3,2	6.5	218
18RFR		1/2	12,7			3,7 - 6,4		170
19RFR		5/8	15,8			6,8 - 9,6		164
20RFR		3/4	19,0			10,0 - 12,7		143
34RFR		7/8	22,2			13,1 - 15,8		131
21RFR		1"	25,4			16,4 - 19,1		118
22RFR		1 1/4	31,7			22,7 - 25,4		100
23RFR		1 1/2	38,1			29,1 - 31,8		89
24RFR		1 3/4	44,4			35,4 - 38,1		74
25RFR		2"	50,8			41,8 - 44,5		68
26RFR	5/16" - 7,9	3/8	9,5	13.7 - 14.5	5.7 - 6.1	0,8 - 1,6	8.5	124
27RFR		1/2	12,7			1,4 - 4,8		111
28RFR		5/8	15,8			4,6 - 8,0		95
29RFR		3/4	19,0			7,7 - 11,2		93
30RFR		1"	25,4			14,1 - 17,5		70
31RFR		1 1/4	31,7			20,4 - 23,9		60
32RFR		1 1/2	38,1			26,8 - 30,2		53
33RFR		1 3/4	44,4			33,1 - 36,6		47

(\*) Debido a las tolerancias dimensionales, las unidades por kilo pueden presentar variaciones.

